

damp/stain/mould



Silkrete
CONSTRUCTIVE SOLUTIONS



Description

A specially formulated single pack moisture cured polyurethane sealer for sealing concrete rendered ponds under the water line, Silkrete Clear Seal should be used above the waterline and for paving around the pond. For damp proofing internal render, plaster, plasterboard and sealing dusty concrete floors, can be used externally on walls if overpainted to protect from UV. Can be used to coat internal woodwork.

Colours

Clear (Translucent Brown) & Black.

Advantages

- * One pack, ready for use.
- * Hard wearing, durable and long lasting.
- * Non-absorbent, easily cleaned reducing maintenance.
- * Unaffected by water, oils and most common chemicals.
- * Quick and easy application.

Technical Information

Silkrete is an easy to apply liquid polyurethane that forms a hard but a flexible plastic seal on almost any porous surface. Treat your wood, plaster, brick, concrete and more to a coat of armour; sealing out moisture, consolidating fragile surface and leaving a tough, hardwearing glosscoat that can be tiled onto, painted or wallpapered over.

| | |
|---|--|
| Coverage: | 8m ² /Litre per coat. (Depending on substrate) |
| Drying Time: | 45 - 60 minutes @ 20 Degrees C / 70% relative humidity. |
| Full Cure & Chemical resistance: | 72 hours |
| Light Traffic: | 12 hours |
| Shelf Life: | 24 months in unopened sealed container, once opened product will begin to cure. |
| Flash Point: | 27°C |
| Viscosity: | 250-500 cps |
| Specific Gravity: | 0.95 |
| Cleaning: | Clean equipment with Silkrete thinners, Silkrete cleaner or acetone. |
| Preparation: | All surfaces to be coated must be dry and porous new concrete render should be given 21- 28 days to fully cure before coating, if a water proofer has be added to render sand down surface to obtain a key and remove residual water proofer, repair any cracks in the surface before coating, remove any loose plaster. |

Limitations

Damp Sealer is not recommended for hard dense tiles or power floated floors, bitumen, rubber, vinyl and other plastic flooring.

Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty, the user will be deemed to have satisfied themselves independently as to the suitability of our products for their own particular purpose, in no event shall Silkrete be liable for consequential or incidental damages.

Users must always refer to the most recent issue of the technical datasheets, copies of which will be supplied on request.